

elmeg T240

The cost/performance reference class for demanding home office user

T240

Even ISDN novices expect more today from their ISDN system: The new compact PABX system, the elmeg T240 as the successor to the well-known elmeg D@VOS-24.net, combines high performance and new, innovative function in a compact, attractively designed enclosure.



Automatic completion of call, team functions, call forwarding, Day/Night call modes, a freely configurable charge limit for each subscriber (Allowance account) and a central telephone directory with 500 entries all help to professionalize your communication.

Four a/b ports – expandable to six via an optional extra module – utilize CLIP (caller ID) and 12/16 Hz charge pulse, for supporting all current industrial standards for a/b convenience functions. Any type of terminal devices, such as cordless or standard phones, modems, fax devices, answering machines and even door intercom units* can be easily wired and configured.

Link your PC directly to the PABX system via the USB port – ISDN channel bundling permits Internet access at up to 128 kbit/s. You can, of course, also easily configure your system via USB. Computer Telephony Integration (CTI) is easy to implement, thanks to the TAPI and CAPI drivers supplied with the system.

A CD containing configuration software (elmeg Professional Configurator, Telephone directory, Charge and TAPI Manager and LCR-Professional) is included with the system.

Highlights elmeg T240:

- o 1 exchange line ISDN bus
- o 4 analog terminal devices, expandable to 6**
- o Internet access via USB and CAPI driver
- o Operation at analog exchange connections possible*

*) requires compatible TFE or adapter

**) optional extra module

Features elmeg T240

The successor to the well-known elmeg D@vos-24.net. Tried and tested and newcomer in one modern design.

The new, compact PABX system elmeg T240 combines familiar functions and ease of use with new, innovative functions from Elmeg. The system can be expanded by 2 a/b ports, or by a POTS module for connection at an analog exchange connection using this new slot.

Features

- o 2 digital exchange line channels (1 external S0; Point-to-multipoint/ Point-to-point ISDN access)
- o 1 analog exchange line connection (opt. module)
- o max. 6 a/b ports
- o CLIP on all ports
- o USB interface for High speed Plug & Play Internet access (up to 128 KBit/s) and CTI
- o TAPI, CAPI driver
- o LEDs for Power, B1, B2, USB, ISDN/POTS

And also:

- o elmeg WIN Tools *:
- o elmeg Professional Configurator
- o elmeg Telephone Directory Manager
- o elmeg Charge Manager
- o elmeg Web-Interface for LCR-Professional
- o elmeg TAPI Manager
- o elmeg Download-Manager
- o System configuration and firmware updates via USB and from remote locations

*) supplied on CD-ROM

Current features

- o Direct Internet access through USB
- o LCR feature including gateway support
- o Connection of a door terminal adapter to the analog ports
- o Automatic completion of call on busy (CCBS) in the network and internally
- o Individual and team functions busy-on-busy
- o Team calls to an MSN extension number (team number)
- o Deflecting calls without answering (CD, Call deflection)
- o Charge credit for each subscriber (pocket money)
- o CLIP (number display) supported by all analog ports
- o Call rerouting programmable from a remote location (Follow me)
- o Memory for 500 charge data records, overflow indication by LED
- o Centralized switching of day/night modes
- o Day/night call mode controlled by date/time (incl. day of the week control)
- o Speed dial with 500 entries

Accessories

- o elmeg 2 a/b module
- o elmeg 1 POTS module